

Heat Gun 2000W 2 stages RD-HG29

Art. number: **074317**

Barcode: **3800972043367**

✓ The RAIDER RD-HG29 has a power rating of 2000 W and two operating settings for various repair, installation and finishing tasks.

✓ It provides a temperature of up to 350°C with an airflow rate of 300 l/min on the first setting and up to 600°C with an airflow rate of 500 l/min on the second setting.

✓ It is suitable for removing paint and varnish, softening adhesives and processing various materials.



TECHNICAL FEATURES

Parameter	Measure Unit	Value
Air flow work rate at at stage i (l/min)	l/min	300
Air flow work rate at at stage ii (l/min)	l/min	500
Maximum delivery rate (l/min)	l/min	500
Rated input power (W)	W	2000
Rated voltage (V)	V	230
Number of air volume levels		2
Number of air temperature levels		2
Output nozzle temperature @ stage i (°C)	°C	350
Output nozzle temperature @ stage ii (°C)	°C	600
Rated voltage type	Corded - Electrical Grid	

LOGISTICS INFORMATION

Type of package	Quantity	Width Length Height	Volume	Net Brutto Tara	Barcode
pieces	1 pieces	7.7 x 23.5 x 25.4213 cm	0.00460 m3	0.8000 - 0.9000 - 0.1000 kg	3800972043367
carton	10 pieces	25 x 40 x 46 cm	0.04600 m3	9.0000 - 9.0000 - 0.0000 kg	38009720433672